



## Short Facts

### Performance

Output approx. (in srm)	-
Green waste	170
Bark	220
Scrap wood	110
Household waste	-

### Infeed

Feeding width (in mm)	1500
Feeding height (in mm)	820
Infeed conveyor length (in mm)	4000
Silo capacity (in m³)	6

### Grinding unit

Rotor diameter (in mm)	1040
Number of hammers	38

### Material outfeed via conveyor belt

Discharge height (in mm)	3200
--------------------------	------

### Main drive

Diesel engine	Mercedes-Benz OM 460 LA Euromot 3B
Electric motor	-
Power (in kW/PS)	375 / 510

### Carriage

Top speed (in km/h)	80
---------------------	----

### Weight

Weight basic model (in kg)	20000
Permitted axle load (in kg)	20000
Permitted support load (in kg)	1000
Permitted total weight (in kg)	21000

### Measurements transport position

Length (in mm)	10900
Width (in mm)	2550
Height (in mm)	3970

### Control system

JES	
VARIO-Flex	✓
IBC	✓
DIP	✓
Sensotronic	✓
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
15-channel remote control	✓
IPS	✓



### Application

- Ideal machine for changing applications
- composting (grass cutting, bio-waste)
- trunk wood, roots, scrap wood
- substrate regrinding in biogas plants

### Specifics

- Varioflex control for economic operation
- variable applications by Twin-Gear drive for optimal rotor speed
- Easy system for simple tool change by just one person
- IPS Impact protection system
- 3-axes chassis for maximum load capacity

## JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14  
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0  
E-Mail: [info@jenz.de](mailto:info@jenz.de)