



short facts

Performance

| | |
|--|-----|
| Max.diameter hardwood (in cm) (in cm) | 42 |
| Max.diameter softwood (in cm) (in cm) | 56 |
| Output approx. (in srm) | 120 |

Intake opening

| | |
|------------------------|-----|
| Feeding width (in mm) | 790 |
| Feeding height (in mm) | 650 |

Grinding unit

| | |
|---|--------|
| Rotor diameter (in mm) | 820 |
| Number of blades (half / full equipment) (in cm) | 8 (16) |

Material outfeed

| | |
|-----------------------|---|
| Blower outfeed | ✓ |
| Conveyor belt outfeed | - |

Main drive

| | |
|---------------------------|-------------|
| Diesel engine | MAN, Euro 6 |
| Electric motor | - |
| (in kW/PS) | 265 / 360 |
| Power requirement (in kW) | - |

Carriage

| | |
|---------------------|----|
| Number of axles | 3 |
| Top speed (in km/h) | 80 |

Weight (without crane)

| | |
|--------------------------------|-------|
| Weight basic model (in kg) | 20000 |
| Permitted axle load (in kg) | 26000 |
| Permitted support load (in kg) | - |
| Permitted total weight (in kg) | 26000 |

Measurements transport position

| | |
|----------------|------|
| Length (in mm) | 7500 |
| Width (in mm) | 2550 |
| Height (in mm) | 3800 |

Control system

| | |
|----------------------------------|---|
| easygreen | ✓ |
| DIP | ✓ |
| Sensotronic | - |
| Automatic overload control unit | ✓ |
| Infeed speed stepless adjustable | ✓ |
| Wire-remote control | - |
| 15-channel remote control | - |
| Z-Tronic | - |



Application

- shrubs and standing timber up to approx. 560 mm diameter
- alternative to tractor with power takeoff shaft chipper
- ideal machine for small jobs
- ideal for working in restricted spaces
- large deployment radius

Specifics

- smallest and lightest JENZ chippertruck
- low purchase and operating costs
- chipper drive via HGV motor
- large screen area for best chipping quality
- comfortable working position
- 80 km/h top speed

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de