



short facts

Performance

Max.diameter hardwood (in cm) (in cm)	45
Max.diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	200

Intake opening

Feeding width (in mm)	1200
Feeding height (in mm)	680

Grinding unit

Rotor diameter (in mm)	820
Number of blades (half / full equipment) (in cm)	12 (24)

Material outfeed

Blower outfeed	✓
Conveyor belt outfeed	-

Main drive

Diesel engine	Mercedes Benz, OM 471 LA
Electric motor	-
(in kW/PS)	390 / 530
Power requirement (in kW)	-

Carriage

Number of axles	2
Top speed (in km/h)	80

Weight (without crane)

Weight basic model (in kg)	16500
Permitted axle load (in kg)	18000
Permitted support load (in kg)	2000
Permitted total weight (in kg)	20000

Measurements transport position

Length (in mm)	8300
Width (in mm)	2550
Height (in mm)	3700

Control system

easygreen	✓
DIP	✓
Sensotronic	✓
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	-



Application

- shrubs and standing timber up to approx. 560 mm diameter
- high-powered chipping independent of towing vehicle

Specifics

- driver via high-powered add-on motor
- 1.20 m wide draw-in makes processing of bulky material easier
- extra-large screen area for best chipping quality
- enormous screen basket cover swivel capability for optimal accessibility of rotor and screen basket changing without tools
- material outfeed via blower and/or conveyor belt

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de